

## SuperCenter – a neat and clean solution!



## Modern powder logistic –

## monitoring of color change and powder consumption!

The new WAGNER SuperCenter is benchmark and trendsetter for powder supply logistics equipment. Our product philosophy combines high coating quality, reduction of time, process reliability and process cost monitoring. Clean and easy to use, the new SuperCenter fulfills the demands of the modern workplace and ensures constant and high quality coating results.

- Central operation with high-resolution color touch screen includes understandable symbols and clear text command buttons or messages for secure operation.
- Documentation of the powder consumption for each color change and easily selectable coating periods can be used to monitor the coating performance and provide a calculation base for the coating cost. Powder consumption data can be downloaded via USB interface and edited on a PC or laptop.
- Automatic color change with interactive user guidance. Color change is as easy as a walk in the park.
- Different operational modes allow for the regular changing demands of a job coater. Standard mode, short batch mode, spray to waste or spray to recovery (with selectable automatic change from spray to waste) ensure optimal operational sequences and a minimum time required for color change in each situation.

# The color change multi-talent!



Automatic powder box changing – complete without down time!

Superior finishing quality by PI-F1 or HiCoat-ED powder pumps



## Available operation modes:

- Standard coating including fresh powder supply
- Short batch coating without fresh powder supply
- Manual operation
- Spray to waste and spray to recovery
- Automatic change from spray to waste to recovery with selectable delaytime
- Set-up mode
- Powder output measurement function
- Color change, automatic process with on-screen dialogue to the operator

Technical Data	SuperCenter
<b>Dimensions</b>	
<b>Weight</b>	2150 mm
<b>Hight</b>	2100 mm
<b>Depth</b>	1330/1500 mm
<b>Weight</b>	approx. 500 kg
<b>Connections</b>	
<b>Electrical</b>	220 V, 50/60 Hz
<b>Pneumatic</b>	1", 6-8 bar
<b>Exhaust connection</b>	To final filter, duct diameter 280 mm
<b>Equipment</b>	
<b>Max. number of guns</b>	18
<b>Typ of powder pumps</b>	PI-F1 or HiCoat-ED
<b>Powder supply</b>	Fluidized container, max. 5 kg powder amount, inspection possible
<b>Fresh powder supply</b>	Integrated, feeding with IP5000 out of 20 kg powder box
<b>Operation</b>	High resolution 8" Color touchscreen
<b>Powder consumption data download</b>	USB interface, clear text format, editing with MS-Excel®



Pumps and feed hoppers are visible and automatically cleaned.



J. Wagner GmbH  
Industrial Solutions  
D-88677 Markdorf  
Tel. +49 (0) 75 44/5 05-0  
Fax +49 (0) 75 44/5 05-200

J. Wagner AG  
Industrial Solutions  
CH-9450 Altstätten/SG  
Tel. +41 (0) 71/7 57 22 11  
Fax +41 (0) 71/7 57 23 23

[www.wagner-group.com](http://www.wagner-group.com)